



GP 3-5ton Telescopic forklift

specification

	Model		GTF30	GTF35	GTF50	
1	Rated load	kg	3000	3500	5000	
2	Max lift height	mm	6800	6800	10000	
3	Max forward reach	mm	3930	3930	6800	
4	Overall length (to fork rack)	mm	5050	5050	6080	
5	Overall width	mm	2260	2260		
6	Overall height	mm	2490	2490	2540	
7	Wheelbase	mm	2800	2800	3300	
8	Ground clearance	mm	360	360	400	
9	Minimum turning radius	mm	3800	3800	4000	
10	weight no load	kg	7380	7380	11200	
11	Cab width	mm	900	900	900	
12	tyre model		16/70-20		16/70-24	
13	fork specification	mm	1220*125*45		1220*145*55	
14	Lifting time	s	7.2	7.2	7.2	
15	Descending time	s	5.5	5.5	5.5	
16	Extension time	s	6.5	6.5	6.5	
17	Retraction time	s	5.4	5.4	5.4	
18	Up-tipping (loading) time	s	2.9	2.9	2.9	
19	Tipping down (unloading) time	s	2.8	2.8	2.8	
20	Engine	model	Yuchai-YC4DK90-T304/Cummins/Yanmar/Xinchai			
21		Number of cylinders	pcs	4	4	4
22		power	kw	66	66	66
23		displacement	L	3.62	3.62	3.62
24		Maximum torque	N.m	350	350	350
25	Transmission system	Transmission mode	Hydrostatic		Torque converter	
26		Shift number	F2/R2	F2/R2	F2/R2	
27		Max travel speed	Km/h	32	32	34
28		Braking mode	Double-shaft oil invasion, multi-disk type			
29	Hydraulic oil	L	380	380	450	
30	Fuel oil	L	170	170	260	

